


SANIFORM PLUS NO OVERFLOW

- one-seater bath with waste at foot end
- classic four-cornered model
- made of Kaldewei steel enamel 3.5 mm
- **30 YEAR WARRANTY**



Model No.		360-1	361-1	362-1	363-1	372-1	373-1	375-1
External length	a	1400	1500	1600	1700	1600	1700	1800 mm
External width	b	700	700	700	700	750	750	800 mm
Depth	c	410	410	410	410	410	410	430 mm
Internal length (top)	d	1230	1330	1430	1530	1430	1530	1630 mm
Internal length (bottom)	e	850	950	1050	1150	1050	1150	1250 mm
Internal width (top)	f ₁ ; f ₂	550; 530	550; 530	550; 530	550; 530	600; 580	600; 580	675; 640 mm
Internal width (bottom)	g ₁ ; g ₂	390; 350	390; 350	390; 350	390; 350	440; 400	440; 400	520; 450 mm
Height with feet	h	545-560	545-560	545-560	545-560	545-560	545-560	555-560 mm
Height of rim	i	32	32	32	32	32	32	32 mm
Distance top edge to centre of overflow hole	j	63	63	63	63	63	63	75 mm
Distance bath edge to centre of drain hole	k	310	320	310	310	310	310	310 mm
Diameter of overflow hole	l	52	52	52	52	52	52	52 mm
Diameter of drain hole	m	52	52	52	52	52	52	52 mm
Distance foot end of bath edge to centre of foot	n	455	445	450	450	445	445	470 mm
Distance between the feet	o	445	555	600	740	640	750	830 mm
Max. width of feet	p	380	380	380	380	430	430	480 mm
Distance bath edge (foot end) to where handle starts	q	484,5	534,5	584,5	634,5	584,5	634,5	684,5 mm
Distance bath edge (foot end) to where handle ends	r	758,5	808,5	858,5	908,5	858,5	908,5	958,5 mm
Width of rim (foot end; lengthwise)	s ₁ ; s ₂	70; 75	70; 75	70; 75	70; 75	70; 75	70; 75	70; 75 mm
Distance between centre holes	u	212	222	212	212	218	218	216 mm
Water volume** in litres		67	82	93	111	107	123	150
Weight of the enamelled bath in kg		40	40	47	48	47	50	55
Anti-slip		288	288	288	288	288	288	288 mm
Full anti-slip		600 x 220	600 x 220	600 x 220	850 x 240	600 x 220	900 x 300	900 x 300 mm

KALDEWEI